

## DCS-F1722

# 1080P Hybrid Analogue Large Bullet

### Features

- 1/2.9" Sony Progressive Scan CMOS
- 2.8-12mm
- Full HD 1080P
- Video Transmission 300m
- IR Up to 35m
- 2D/3D DNR,dWDR,ICR,HLC,Mirror,Defog, Privacy Masking, Motion Detection
- Support AHD/TVI/CVI/CVBS Output
- IP66



### Technical Specifications

Camera		General	
Image Sensor	• 1/2.9" Sony CMOS	Power Supply	• DC12V±10%
Signal System	• PAL/NTSC	Power Consumption	• 4W(Max)
Min. illumination	• Color:0.01Lux@(F1.2,AGC ON) ; B/W:0Lux@(IR LED ON)	Operating Temperature	• -10°C ~ 55°C (14°F ~ 131°F)
S/N Ratio	• ≥50dB	Operating Humidity	• 0% - 85% RH
Day & Night	• ICR	Ingress Protection	• IP66
Shutter Speed	• PAL:1/50-1/50000 NTSC:1/60-1/60000	Approvals	• CE / FCC
Wide Dynamic Range	• dWDR	Material	• Aluminium Alloy
Digital Noise Reduction	• 2D/3D	Product Dimensions	• Φ228×69mm
Lens	• 2.8-12mm	Product Weight	• 520g
FOV	• 90°~ 35°	<b>Video Output</b>	
IR LED	• 24pcs	Max Distance	• 75-5 300m
IR Wavelength	• 850nm	Video Output	• AHD/TVI/CVI/CVBS
IR Range	• Up to 35m	<b>Dimensions (mm)</b>	
OSD Joystick	• Optional		
Up the Coax	• Support		
<b>Image</b>			
Effective Resolution	• 1920x1080		
Frame	• PAL:25fps ,NTSC:30fps		
Mirror	• Support		
Defog	• Support		
HLC	• Support		
Private Masking	• Support		
Motion Detection	• Support		